

Exam : SUN 310-035

**Title : Sun Certified Programmer
For The Java 2 Platform 1.4**

Version : Demo

Important Note, Please Read Carefully

Other VisualExams products

[All visual exams IT Exam Products](#)

Our products of Offline Testing Engine

Use the offline Testing engine product to practice the questions in an exam environment.

Build a foundation of knowledge which will be useful also after passing the exam.

[visual exams Testing Engine](#)

Latest Version

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 90 days after the purchase. You should check your member zone at VisualExams and update 3-4 days before the scheduled exam date.

Here is the procedure to get the latest version:

1. Go to <http://www.visual exams.com/>
2. Log in the **User Center**
3. The latest versions of all purchased products are downloadable from here. Just click the links.

Feedback

If you spot a possible improvement then please let us know. We always interested in improving product quality.

Feedback should be send to Visual exams@hotmail.com. You should include the following: Exam number, version, page number, question number, and your login Account.

Our experts will answer your mail promptly.

Explanations

This product does not include explanations at the moment. If you are interested in providing explanations for this exam, please contact Visual exams@hotmail.com.

Features

- Comprehensive questions with complete details
- Instant Downloadable in PDF form.
- Verified Answers Researched by Industry Experts
- Questions accompanied by exhibits.
- Drag and Drop questions as experienced in the Actual Exams.
- These questions and answers are backed by our GUARANTEE.
- Questions updated on regular basis.
- Like actual certification exams our product is in multiple-choice questions (MCQs)

Commitment to Your Success: At VisualTestExam.com, we are committed to you ongoing success. Our exams and questions are constantly being updated and compared to industry standards.

Want to earn a Microsoft certification like MCSE, MCSE 2003, CCNA, CCNP? Thinking about getting an A+ or CCSP?

A, CCSP or Network+ Certification with less effort and time. You will be astonished at the theoretical and practical knowledge you will acquire in such a short period of time using our Certification Training Products. Our Study material will enable you to pass your Microsoft, Your Cisco and any other certification on the very first attempt.

Guarantee

Visualexams provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if somehow you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

1. Click the Exhibit button.

What is the result when main is executed?

```
1. class A {
2.     public A() {
3.         System.out.println("hello from a");
4.     }
5. }
6. class B extends A {
7.     public B() {
8.         System.out.println("hello from b");
9.         super();
10.    }
11. }
12. public class Test {
13.     public static void main(String args[])
14.     {
15.         A a = new B();
16.     }
```

A. Compilation fails.

B. hello from a

C. hello from b

D. hello from b

hello from a

E. hello from a

hello from b

Answer: A

2. Click the Exhibit button.

What is the result?

```
1. class A {
2.     public int getNumber(int a) {
3.         return a + 1;
4.     }
5. }
6.
7. class B extends A {
8.     public int getNumber(int a, char c) {
9.         return a + 2;
10.    }
11.
12.    public static void main(String args[])
13.    {
14.        B b = new B();
15.        System.out.println(b.getNumber(0));
16.    }
```

- A. 1
- B. 2
- C. Compilation fails because of an error in line 8.
- D. Compilation fails because of an error in line 14.

Answer: A

3. Given:

```
1. public class ConstOver {
2.     public ConstOver(int x, int y, int z) {
3.     }
4. }
```

Which two overload the ConstOver constructor? (Choose two.)

- A. ConstOver() { }
- B. protected int ConstOver() { }
- C. private ConstOver(int z, int y, byte x) { }
- D. public Object ConstOver(int x, int y, int z) { }
- E. public void ConstOver(byte x, byte y, byte z) { }

Answer: AC

4. Given:

```
1. class Passenger { }
2. class Engine { }
3. interface TransportVehicle {
4.     void loadPassengers();
5. }
6. interface Helicopter extends TransportVehicle {
```

- ```
7. int flyIt(String direction);
8. }
9. abstract class JetStream implements Helicopter { }
```

Which statement is correct?

- A. TransportVehicle has a Passenger.
- B. Engine is encapsulated in the JetStream class.
- C. Interface TransportVehicle forms the basis for polymorphic actions.
- D. Non-abstract classes extending JetStream can optionally provide a method definition for the loadPassengers() method.

**Answer: C**

5. Given:

- ```
1. public class MyCircle {  
2.     public double radius;  
3.     public double diameter;  
4.     public void setRadius(double radius) {  
5.         this.radius = radius;  
6.         this.diameter = radius * 2;  
7.     }  
8.     public double getRadius() {  
9.         return radius;  
10.    }  
11. }
```

Which statement is true?

- A. The MyCircle class is fully encapsulated.
- B. The diameter of a given MyCircle is guaranteed to be twice its radius.
- C. Lines 5 and 6 should be in a synchronized block to ensure encapsulation.
- D. The radius of a MyCircle object can be set without affecting its diameter.

Answer: D

6. Given:

- ```
1. public class Outer {
2. public static class StaticInner {
3. }
4. }
```

Which two statements are true? (Choose two.)

- A. Class StaticInner requires a static initializer.

- B. Class StaticInner requires an instance of class Outer.
- C. Class StaticInner has no reference to an instance of class Outer.
- D. Class StaticInner has access to the non-static members of class Outer.
- E. Static members of class StaticInner can be referenced using the class name Outer.StaticInner.

**Answer: CE**

7. Given:

```
12. void start() {
13. A a = new A();
14. B b = new B();
15. a.s(b);
16. b = null;
17. a = null;
18. System.out.println("start completed");
19. }
```

When is the B object, created in line 14, eligible for garbage collection?

- A. after line 16
- B. after line 17
- C. after line 18 (when the method ends)
- D. There is no way to be absolutely certain.
- E. The object is NOT eligible for garbage collection.

**Answer: D**

8. Click the Exhibit button.

Which two statements are correct? (Choose two.)

```
1. class A {
2. }
3. class Alpha {
4. private A myA = new A();
5.
6. void doIt(A a) {
7. a = null;
8. }
9. void tryIt() {
10. doIt(myA);
11. }
12. }
```

- A. There are no instances of A that will become eligible for garbage collection.
- B. Explicitly setting myA to null marks that instance to be eligible for garbage collection.
- C. Any call on tryIt() causes the private instance of A to be marked for garbage collection.

D. Private instances of A become eligible for garbage collection when instances of Alpha become eligible for garbage collection.

**Answer: BD**

9. Which statement is true?

A. Memory is reclaimed by calling Runtime.gc().

B. Objects are not collected if they are accessible from live threads.

C. Objects that have finalize() methods are never garbage collected.

D. Objects that have finalize() methods always have their finalize() methods called before the program ends.

E. An OutOfMemory error is only thrown if a single block of memory cannot be found that is large enough for a particular requirement.

**Answer: B**

10. Which statement is true?

A. To call the wait() method, a thread must own the lock of the current thread.

B. To call the wait() method, a thread must own the lock of the object on which the call is to be made.

C. To call the join() method, a thread must own the lock of the object on which the call is to be made.

D. To call the sleep() method, a thread must own the lock of the object on which the call is to be made.

E. To call the yield() method, a thread must own the lock of the object on which the call is to be made.

**Answer: B**

11. Which two conditions can place the thread in a runnable state after wait() has been called on an object in that thread? (Choose two.)

A. A thread calls resume() on the thread.

B. A higher priority thread invokes yield().

C. A higher priority thread invokes sleep();

D. A thread calls notify() on the same object.

E. A thread calls notifyAll() on the same object.

**Answer: DE**

12. Given:

```
1. public class Foo implements Runnable {
2. public void run() {
3. System.out.println("Running");
4. }
5. public void start() {
6. System.out.println("Starting");
7. }
```

```
8. public static void main(String[] args) {
9. new Thread(new Foo()).start();
10. }
11. }
```

What is the result?

- A. Running
- B. Starting
- C. Compilation fails.
- D. The code runs with no output.
- E. An exception is thrown at runtime.

**Answer: A**

13. Which two statements are true? (Choose two.)

- A. The wait method can be called with a timeout parameter.
- B. The notify method can be invoked on a specific thread of execution.
- C. The wait method need not be called from within a synchronized context.
- D. The wait and notify methods are defined in class java.lang.Thread.
- E. The wait and notify methods are defined in class java.lang.Object.
- F. The notify method releases the object's lock regardless of when it is called.

**Answer: AE**

14. Click the Exhibit button.

Which statement at line 17 will ensure that j = 10 at line 19?

```
1. class A implements Runnable {
2. int i;
3. public void run() {
4. try {
5. Thread.sleep(5000);
6. i = 10;
7. } catch(InterruptedException e) {}
8. }
9. }
10.
11. public class Test {
12. public static void main(String args[])
13. {
14. try {
15. A a = new A();
16. Thread t = new Thread(a);
17. t.start();
18. int j = a.i;
19. }
20. } catch(Exception e) {}
21. }
22. }
```

- A. a.wait();
- B. t.wait();
- C. t.join();
- D. t.yield();
- E. t.notify();
- F. a.notify();
- G. t.interrupt();

**Answer: C**

15. Which statement is true?

- A. To call the join() method, a thread must own the lock of the current thread.
- B. To call the sleep() method, a thread must own the lock of the current thread.
- C. To call the yield() method, a thread must own the lock of the current thread.
- D. To call the notify() method, a thread must own the lock of the current thread.
- E. To call the notify() method, a thread must own the lock of the object on which the call is to be made.

**Answer: E**

16. Thread Z holds the lock on object A. Thread X is blocked inside a wait call on object A. What allows thread X to become runnable?

- A. Thread X is interrupted.
- B. Thread Z is interrupted.
- C. Thread X's wait() times out.
- D. Thread Z calls Thread.sleep(100);
- E. Thread Z releases the lock on A and calls the notify() method on thread X.
- F. Thread Z releases the lock on A and calls the notifyAll() method on object A.

**Answer: F**

17. Click the Exhibit button.

Which is the output from this code?

```
1. class Worker implements Runnable {
2.
3. Worker(String name) {
4. new Thread(this, name).start();
5. }
6.
7. public void run() {
8. System.out.println(Thread.currentThread()
getName());
9. }
10. }
11.
12. class Alpha2 {
13. public static void main(String[] args
) {
14.
15. Thread.currentThread().setName("Main");
16. Runnable r = new Worker("Worker");
17. r.run();
18. }
```

- A. Main
- B. Worker
- C. Main Worker
- D. Worker Main
- E. indeterminate
- F. The code runs with no output.

**Answer: E**

18. Given:

```
11. try {
12. if ((new Object()).equals((new String("x")))) {
13. System.out.println("equal");
14. } else {
15. System.out.println("not equal");
16. }
17. } catch (Exception e) {
18. System.out.println("exception");
19. }
```

What is the result?

- A. equal
- B. not equal

- C. exception
- D. Compilation fails.

**Answer: B**

19. Given:

```
11. int i = 0, j = 1;
12. if ((i++ == 1) && (j++ == 2)) {
13. i = 42;
14. }
15. System.out.println("i = " + i + ", j = " + j);
```

What is the result?

- A. i = 1, j = 2
- B. i = 1, j = 1
- C. i = 42, j = 2
- D. i = 42, j = 1
- E. Compilation fails.

**Answer: B**

20. Given:

```
1. public class X {
2. public static void main(String[] args) {
3. byte b = 127;
4. byte c = 126;
5. byte d = c - b;
6. System.out.println("d = " + d);
7. }
8. }
```

What is the result?

- A. d = -1
- B. d = 255
- C. Compilation fails.
- D. An exception is thrown at runtime.

**Answer: C**

Visualexams.com was founded in 2006. The safer,easier way to help you pass any IT Certification exams . We provide high quality IT Certification exams practice questions and answers(Q&A). Especially Adobe, Apple, Citrix, Comptia, EMC, HP, HuaWei, LPI, Nortel, Oracle, SUN, Vmware and so on. And help you pass any IT Certification exams at the first try.

Web site: <http://www.visualexams.com>

You can reach us at any of the email addresses listed below.

E-Mail: [visualexams \(at\) hotmail.Com](mailto:visualexams@hotmail.com)