

Exam : SUN 310-230

**Title : Sun Certified Developer for
Java Web Services**

Version : Demo

Important Note, Please Read Carefully

Other VisualExams products

[All visual exams IT Exam Products](#)

Our products of Offline Testing Engine

Use the offline Testing engine product to practice the questions in an exam environment.

Build a foundation of knowledge which will be useful also after passing the exam.

[visual exams Testing Engine](#)

Latest Version

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 90 days after the purchase. You should check your member zone at VisualExams and update 3-4 days before the scheduled exam date.

Here is the procedure to get the latest version:

1. Go to <http://www.visual exams.com/>
2. Log in the **User Center**
3. The latest versions of all purchased products are downloadable from here. Just click the links.

Feedback

If you spot a possible improvement then please let us know. We always interested in improving product quality.

Feedback should be send to Visual exams@hotmail.com. You should include the following: Exam number, version, page number, question number, and your login Account.

Our experts will answer your mail promptly.

Explanations

This product does not include explanations at the moment. If you are interested in providing explanations for this exam, please contact Visual exams@hotmail.com.

Features

- Comprehensive questions with complete details
- Instant Downloadable in PDF form.
- Verified Answers Researched by Industry Experts
- Questions accompanied by exhibits.
- Drag and Drop questions as experienced in the Actual Exams.
- These questions and answers are backed by our GUARANTEE.
- Questions updated on regular basis.
- Like actual certification exams our product is in multiple-choice questions (MCQs)

Commitment to Your Success: At VisualTestExam.com, we are committed to you ongoing success. Our exams and questions are constantly being updated and compared to industry standards.

Want to earn a Microsoft certification like MCSE, MCSE 2003, CCNA, CCNP? Thinking about getting an A+ or CCSP?

A, CCSP or Network+ Certification with less effort and time. You will be astonished at the theoretical and practical knowledge you will acquire in such a short period of time using our Certification Training Products. Our Study material will enable you to pass your Microsoft, Your Cisco and any other certification on the very first attempt.

Guarantee

VisualExams provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if somehow you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

1. Which two statements are true about XML schemas and WSDL 1.1? (Choose two.)

- A. <http://schemas.xmlsoap.org/wsdl/> is the WSDL namespace for SOAP binding.
- B. xsi is used as a prefix to represent the schema namespace as defined by XSD.
- C. XSD schemas are used as a formal definition of WSDL grammar.
- D. xsd is used as a prefix to represent the schema namespace as defined by XSD.
- E. <http://schemas.xmlsoap.org/wsdl/http/> is the WSDL namespace for SOAP binding.

Answer: CD

2. A company's new investment management Java application and a legacy stock trader application need to communicate, but they use different JMS implementations. A developer decides to implement a JMS bridge to solve the problem.

Which two advantages does this pattern provide? (Choose two.)

- A. It converts the interface of a class into another interface that clients expect.
- B. It decouples an abstraction from its implementation so that the two can vary independently.
- C. It dynamically attaches additional responsibilities to an object.
- D. It optimizes network traffic.
- E. It is vendor independent.

Answer: BE

3. Which situation requires the client to use the Dispatch interface to access the Web service?

- A. The client and the server are on different platforms.
- B. The client has access to the portable artifacts, but not to the WSDL.
- C. The client has access to the WSDL, but not to the portable artifacts.
- D. The client will access a REST-based service.

Answer: D

4. What are two features of a WSDL 1.1 document? (Choose two.)

- A. Service defines a collection of related endpoints.
- B. Service describes the message's payload using XML.
- C. Service assigns an Internet address to a specific binding.

- D. Porttype declares complex data types and elements used elsewhere.
- E. Porttype elements are used to group a set of abstract operations.
- F. Porttype defines a concrete protocol and data format specification.

Answer: AE

5. Which three can an EJB-based endpoint use? (Choose three.)

- A. HTTP sessions
- B. Java EE 5 declarative security
- C. Java EE 5 programmatic security
- D. client-demarcated transactions
- E. container-managed transactions

Answer: BCE

6. What are two communication modes supported by JAX-WS? (Choose two.)

- A. Synchronous RPC
- B. Dynamic Service Binding
- C. Dynamic Proxy
- D. Endpoint Invocation
- E. Dispatch

Answer: CE

7. A company is refactoring an existing website to use Web services clients. The application retrieves lists of parts and displays them to the users in a browser window. Previously, the data was stored as files on the web server and, in order to access the files, the user would simply click on a hyperlink. Now the data must be dynamically generated via a service that another developer has created. They want the easiest way to refactor their website to use Web services.

Which three technologies should they use? (Choose three.)

- A. SOAP
- B. REST
- C. Javascript

- D. XML
- E. JSON
- F. Java

Answer: BCE

8. A JAXR client has established connection with a UDDI registry and needs to get a service binding from the registry.

What is required to accomplish this task?

- A. find the appropriate concept and then find the service binding associated with that concept
- B. find the appropriate authentication token and then find the service binding associated with that authentication token
- C. find the appropriate organization, get the tModel associated with that organization, and then find the service binding associated with the tModel
- D. find the appropriate organization, find the services associated with that organization, and then find the service binding associated with the service

Answer: D

9. What are three benefits of using SSL to connect to a Web service without mutual authentication? (Choose three.)

- A. The server is assured of the client's identity if the client issues the certificate.
- B. The client is assured of the server's identity.
- C. Message integrity is preserved between the client and the server.
- D. The communication between the client and the server is still logged.
- E. The communication between the client and the server is encrypted.
- F. Using SSL over HTTP incurs less overhead than HTTPS.

Answer: BCE

10. A developer is creating a servlet-based endpoint for a new payroll application.

What are three requirements for the service? (Choose three.)

- A. It needs to be packaged as a WAR file.

- B. It needs to be packaged as a JAR file.
- C. It requires a META-INF folder.
- D. It requires a WEB-INF folder.
- E. webservices.xml is required.
- F. web.xml is required.

Answer: ADF

11. A developer is creating an XML schema that is Basic Profile compliant, and has elements that require long integer values.

Given the code:

```
<Schema targetNamespace="http://sun.cert/types"
xmlns:ns0="http://www.w3.org/2001/XMLSchema"
xmlns="http://www.w3.org/2001/XMLSchema"
xmlns:xsd="http://sun.cert/xsdTypes"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<complexType name="Foo">
<sequence>
<!-- insert code here -->
</sequence>
</complexType>
</schema>
```

Assuming that no other namespace declarations exist, which two elements use the long type that is defined in the http://www.w3.org/2001/XMLSchema namespace? (Choose two.)

- A. <element name="length" type="long"/>
- B. <element name="length type="xsi:long"/>
- C. <element name="length" type="xsd:long"/>
- D. <element name="length" type="ns0:long"/>
- E. <element name="length" type="integer"/>
- F. <element name="length" type="xsd:integer"/>

Answer: AD

12. A developer needs to define an array of long integers in their Basic Profile compliant Web service and is given the following code fragment for analysis:

```
<Schema targetNamespace="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:wSDL="http://schemas/xmlsoap.org/wSDL">
<!-- insert code here -->
</schema>
```

Assume all XML fragments are well-formed.

According to the WS-I Basic Profile 1.1, which type definition can be used to define an array of longs?

A. `<xsd:complexType name="longArray">`

```
<xsd:array>
<xsd:element name="item" type="xsd:long"/>
</xsd:array>
</xsd:complexType>
```

B. `<xsd:complexType name="longArray">`

```
<xsd:sequence>
<element name="item" type="xsd:long"/>
</xsd:sequence>
</xsd:complexType>
```

C. `<xsd:complexType name="longArray">`

```
<xsd:array>
<xsd:element name="item" type="xsd:long" minOccurs="0"
maxOccurs="unbounded"/>
</xsd:array>
</xsd:complexType>
```

D. `<xsd:complexType name="longArray">`

```
<xsd:sequence>
<xsd:element name="item" minOccurs="0" maxOccurs="5"
```

```
type="xsd:long"/>
</xsd:sequence>
</xsd:complexType>
E. <xsd:complexType name="longArray">
<xsd:sequence>
<xsd:element name="item" minOccurs="0" maxOccurs="5"
type="xsd:integer"/>
</xsd:sequence>
</xsd:complexType>
```

Answer: D

13. A developer is creating an XML schema using the xsd:all operator.

Given the code:

```
<types>
<schema targetNamespace="http://sun.cert/types"
xmlns:tns="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<xsd:complexType name="Person">
<xsd:all>
<!-- insert code here -->
</xsd:all>
</xsd:complexType>
</schema>
</types>
```

Which two element definitions, when inserted into the given schema fragment, result in a correct schema type definition? (Choose two.)

- A. <xsd:element name="first" type="xsd:string"/>
- B. <xsd:element name="items" type="xsd:long" maxOccurs="5"/>
- C. <xsd:element name="last" type="xsd:string" minOccurs="1" maxOccurs="1"/>
- D. <xsd:element name="first" type="xsd:string" minOccurs="0" maxOccurs="5"/>

E. <xsd:element name="last" type="xsd:string" minOccurs="1" maxOccurs="5"/>

F. <xsd:element name="ssn" type="xsd:string" minOccurs="1" maxOccurs="unlimited"/>

Answer: AC

14. A developer must create a new stock monitoring application using SOAP.

Given the code:

```
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/"
```

```
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
```

```
xmlns:ns1="http://sun.cert/">
```

```
<s:Header>
```

```
<ns1:transaction>
```

```
<user>root</user>
```

```
<transid>9b3e64e326537b4e8c0ff19e953f9673</transid>
```

```
</ns1:transaction>
```

```
</s:Header>
```

```
<s:Body>
```

```
<m:StockQuote xmlns:m="http://sun.cert/bar/">
```

```
<Quote>
```

```
<ns1:symbol>SUNW</ns1:symbol>
```

```
<ns1:companyname name="Sun"/>
```

```
</Quote>
```

```
</s:Body>
```

```
</s:Envelope>
```

Which statement is true about this SOAP message?

- A. It is NOT well-formed.
- B. It contains a mandatory header block.
- C. It is WS-I Basic Profile 1.1 compliant.
- D. It does NOT contain the correct namespace declarations.
- E. The transid should be blowfish encrypted.

F. <http://sun.cert/bar/> is not a valid stock quote service.

Answer: A

15. A team of developers is describing a set of endpoints in their new SOA application.

Given the WSDL extract:

```
<service name="InventoryServices">
  <port name="PurchaseOrder" binding="tns:POBinding">
    <soap:address location="http://192.168.0.2:8080/inventory"/>
  </port>
  <port name="Invoice" binding="tns:InvoiceBinding">
    <soap:address location="http://192.168.0.2:8080/inventory"/>
  </port>
</service>
```

Which statement is true about this WSDL extract?

- A. The extract is WS-I Basic Profile 1.1 compliant because both port element names are different.
- B. The extract is NOT WS-I Basic Profile 1.1 compliant because both port elements point to the same location.
- C. The extract is WS-I Basic Profile 1.1 compliant because both port elements point to different binding elements.
- D. The extract is NOT WS-I Basic Profile 1.1 compliant because it contains two port elements in the same service.
- E. The extract is WS-I Basic Profile 1.1 conformant because both port element names are different.
- F. The extract is WS-I Basic Profile 1.1 conformant because the port, binding, and service element combinations are unique.

Answer: B

16. Which two statements are true about XML schemas that conform to WS-I Basic Profile 1.1? (Choose two.)

- A. A description may use any construct from XML Schema.
- B. A description may use any construct of XML Schema, except for arrays.

- C. A description must use XML Schema recommendations as the basis of user-defined datatypes and structures.
- D. A description may use any construct of XML Schema, except for defining user-defined datatypes and structures.
- E. RESTful XML schemas may also draw from the XML-Rest Schema.

Answer: AC

17. A developer is defining a SOAP binding in the WSDL for their new service.

Which XML fragment is WSDL 1.1 compliant?

- A. `<soap:binding transport=Http://www.w3.org/2001/XMLSchema?style="document"/>`
- B. `<soap:binding transport=Http://schemas.xmlsoap.org/wsdl/soap/?style="document"/>`
- C. `<soap:binding transport=Http://schemas.xmlsoap.org/soap/http?style="document"/>`
- D. `<soap:binding transport=Http://schemas.xmlsoap.org/soap?style="rpc"/>`

Answer: C

18. Which fragment is Basic Profile 1.1 compliant?

- A. `<port name="testWS"> <operation name="runit">`
`<input message="tns:runit"/>`
`<output message="tns:runitResponse"/>`
`</operation>`
`</port>`
`<binding name="testWSPortBinding" type="tns:testWS">`
`.`
`.`
`.`
`<operation name="runit">`

```
<soap:operation soapAction="tns:runit"/>
<input>
<soap:body use="literal"/>
</input>
<output>
<soap:body use="literal"/>
</output>
</operation>
</binding>
B. <portType name="testWS">
  <operation name="runit">
    <input message="tns:runit"/>
    <output message="tns:runitResponse"/>
  </operation>
  <operation name="saveit">
    <input message="tns:saveit"/>
    <output message="tns:saveitResponse"/>
  </operation>
</portType>
<binding name="testWSPortBinding" type="tns:testWS">
  .
  .
  .
  <operation name="runit">
    <soap:operation soapAction="tns:runit"/>
    <input>
    <soap:body use="literal"/>
    </input>
    <output>
    <soap:body use="literal"/>
```

```
</output>
</operation>
</binding>
C. <port name="testWS">
  <operation name="runit">
    <input message="tns:runit"/>
    <output message="tns:runitResponse"/>
  </operation>
</port>
<binding name="testWSPortBinding" type="tns:testWS">
  .
  .
  .
  <operation name="runit">
    <soap:operation soapAction="runit"/>
    <input>
      <soap:body use="literal"/>
    </input>
    <output>
      <soap:body use="literal"/>
    </output>
  </operation>
</binding>
D. <portType name="testWS">
  <operation name="runit">
    <input message="tns:runit"/>
    <output message="tns:runitResponse"/>
  </operation>
</portType>
<binding name="testWSPortBinding" type="tns:testWS">
```

```
.  
. .  
. .  
<operation name="runit">  
<soap:operation soapAction="runit"/>  
<input>  
<soap:body use="literal"/>  
</input>  
<output>  
<soap:body use="literal"/>  
</output>  
</operation>  
</binding>
```

Answer: D

19. for a company's new software, the developers are constructing abstract definitions of the data being communicated by their document style Web service.

Given the targetNamespace:

```
xmlns:xsd="http://sun.com/sample.xsd"
```

Which is a valid wsdl:message containing a wsdl:part?

A. <message name="GetInput">

```
<part name="body" attribute="tns:InputRequest"/>
```

```
</message>
```

B. <message name="GetInput">

```
<part name="body" element="tns:InputRequest"/>
```

```
</message>
```

C. <message name="GetInput">

```
<part name="body" attribute="xsd:InputRequest"/>
```

```
</message>
```

D. <message name="GetInput">

```
<part name="body" element="xsd:InputRequest"/>
```

```
</message>
```

E. <message name="GetInput">

```
<part name="body" element="xsd:string"/>
```

```
</message>
```

F. <message name="GetInput">

```
<part name="body" element="InputRequest"/>
```

```
</message>
```

Answer: D

20. According to the XML-to-Java mappings used by JAX-WS, which three elements or attribute declarations are mapped to a Java primitive wrapper class (for example, java.lang.Short)? (Choose three.)

A. <xsd:element name="age" type="xsd:short" minOccurs="0"/>

B. <xsd:element name="age" type="xsd:short" nillable="true"/>

C. <xsd:element name="age" type="xsd:short" nillable="false"/>

D. <xsd:attribute name="required" type="xsd:boolean" use="optional"/>

E. <xsd:attribute name="required" type="xsd:boolean" use="required"/>

F. <xsd:attribute name="required" type="xsd:boolean" nillable="false"/>

Answer: ABD

Visualexams.com was founded in 2006. The safer,easier way to help you pass any IT Certification exams . We provide high quality IT Certification exams practice questions and answers(Q&A). Especially Adobe, Apple, Citrix, Comptia, EMC, HP, HuaWei, LPI, Nortel, Oracle, SUN, Vmware and so on. And help you pass any IT Certification exams at the first try.

Web site: <http://www.visualexams.com>

You can reach us at any of the email addresses listed below.

E-Mail: [visualexams \(at\) hotmail.Com](mailto:visualexams@hotmail.com)