

**Exam : Nortel 920-133**

**Title : NNCSS Baystack Switching**

**Version : Demo**

## Important Note, Please Read Carefully

### Other VisualExams products

[All visual exams IT Exam Products](#)

### Our products of Offline Testing Engine

Use the offline Testing engine product to practice the questions in an exam environment.

Build a foundation of knowledge which will be useful also after passing the exam.

[visual exams Testing Engine](#)

### Latest Version

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 90 days after the purchase. You should check your member zone at VisualExams and update 3-4 days before the scheduled exam date.

Here is the procedure to get the latest version:

1. Go to <http://www.visual exams.com/>
2. Log in the **User Center**
3. The latest versions of all purchased products are downloadable from here. Just click the links.

### Feedback

If you spot a possible improvement then please let us know. We always interested in improving product quality.

Feedback should be send to [Visual exams@hotmail.com](mailto:Visual exams@hotmail.com). You should include the following: Exam number, version, page number, question number, and your login Account.

Our experts will answer your mail promptly.

### Explanations

This product does not include explanations at the moment. If you are interested in providing explanations for this exam, please contact [Visual exams@hotmail.com](mailto:Visual exams@hotmail.com).

### Features

- Comprehensive questions with complete details
- Instant Downloadable in PDF form.
- Verified Answers Researched by Industry Experts
- Questions accompanied by exhibits.
- Drag and Drop questions as experienced in the Actual Exams.
- These questions and answers are backed by our GUARANTEE.
- Questions updated on regular basis.
- Like actual certification exams our product is in multiple-choice questions (MCQs)

**Commitment to Your Success: At VisualTestExam.com, we are committed to your ongoing success. Our exams and questions are constantly being updated and compared to industry standards.**

Want to earn a Microsoft certification like [MCSE](#), [MCSE 2003](#), [CCNA](#), [CCNP](#)? Thinking about getting an [A+](#) or [CCSP](#)?

A, [CCSP](#) or [Network+](#) Certification with less effort and time. You will be astonished at the theoretical and practical knowledge you will acquire in such a short period of time using our Certification Training Products. Our Study material will enable you to pass your [Microsoft](#), Your [Cisco](#) and any other certification on the very first attempt.

## **Guarantee**

Visualexams provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if somehow you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

1. You are configuring a BayStack 470-48T switch for QoS and it is necessary to implement a meter as follows:

Limit bandwidth utilization to 20 Mbps.

Drop all traffic that exceeds the 20 Mbps threshold.

How do you ensure that traffic that exceeds the 20 Mbps threshold is dropped?

- A. When adding the meter to the policy, set `Out-of-Profile Action` to `Drop_Traffic` .
- B. When defining the Committed Burst Size of the meter, set `Maximum Burst Size` to 0 kbps .
- C. When adding the meter to the interface group, set `Threshold-Exceeded-Traffic` to `Drop` .
- D. When defining the Committed Burst Size of the meter, set `Maximum Burst Size` to 0 kbps and `Duration` to 0 seconds .

**Answer: A**

2. A BayStack 450-24T switch will be added to an existing stack of two BayStack 470-24T switches. The software Release running on the BayStack 450-24T switch is compatible with the software Release running on the BayStack 470-24T switches. To complete the stack creation successfully, which two configuration changes are necessary? (Choose two.)

- A. Set the Unit Select switch on the BayStack 450-24T to the "Off" position.
- B. Set the Unit Select switch on the BayStack 450-24T to "Base" ("On" position).
- C. Set the Stack Mode for all BayStack 470-24T switches to Hybrid and then reset the stack.
- D. Cable the BayStack 450-24T switch into the stack, power off all units, and then power up the stack.
- E. Set the Stack Mode for the Base BayStack 470-24T switch to Hybrid and leave the other BayStack 470-24T switch as Pure.

**Answer: AC**

3. Click the exhibit button.

Given the following BayStack 325-24T switch configuration:

VLAN 10 is a port-based VLAN.

Port 1 is an untagged member of VLAN 10.

Port 5 is a tagged member of VLAN 10.

The device on Port 1 transmits an untagged frame to the device on Port 5. How will an untagged frame be

treated when it reaches Port 5 on this switch?

```
VLAN Port Configuration

Unit          [ 1 ]
Port          [ 1 ]
Filter Tagged Frames: [ No ]
Filter Untagged Frames: [ No ]
Filter Unregistered Frames: [ No ]
Port Name:    [ Unit 1, Port 1 ]
EVID:        [ 10 ]
Port Priority: [ 6 ]
Tagging:     [ Untagged Access ]
AutoPVID:    [ Disabled ]

Use space bar to display choices, press <Return> or <Enter> to select choice
Press Ctrl-R to return to previous menu. Press Ctrl-C to return to Main Menu.

VLAN Port Configuration

Unit          [ 1 ]
Port          [ 5 ]
Filter Tagged Frames: [ No ]
Filter Untagged Frames: [ No ]
Filter Unregistered Frames: [ No ]
Port Name:    [ Unit 1, Port 5 ]
EVID:        [ 10 ]
Port Priority: [ 2 ]
Tagging:     [ Tagged Access ]
AutoPVID:    [ Disabled ]

Use space bar to display choices, press <Return> or <Enter> to select choice
Press Ctrl-R to return to previous menu. Press Ctrl-C to return to Main Menu
```

- A. It will be discarded when it is received.
- B. It will be placed in a hardware-based queue based on Priority 6, it will be tagged, and transmitted out Port 5 with Priority 2.
- C. It will be placed in a hardware-based queue based on Priority 6, it will be tagged, and transmitted out Port 5 with Priority 6.
- D. It will be placed in a hardware-based queue based on Priority 2, it will be tagged, and transmitted out Port 5 with Priority 2.

**Answer: C**

4. Given the following information:

A BayStack 460-24T-PWR switch is being installed.

The switch will be fully populated with all devices requiring Power over Ethernet (PoE).

The switch has been connected to both internal and external power sources.

The switch will be configured through web-based management.

Once you access the BayStack 460 via the `BS460_24T_PWR(config)#poe poe-dc-source` command, which configuration will provide the most power to supply PoE to the connected devices?

- A. `nes` - Set DC power source from NES
- B. `rpsu` - Set DC power source from the rpsu
- C. `baystack10` - Set DC power source from BayStack 10
- D. `unit` - Set power pairs of another unit in a stack

**Answer: A**

5. What is required to apply traffic shaping to an uplink connection from a BayStack 470-48T switch to the Passport 8600 using the Web-based Management System Interface?

- A. a Media Dependent Adapter (MDA)
- B. NO additional equipment is required
- C. a Gigabit Interface Connector (GBIC)
- D. a mini Gigabit Interface Connector (GBIC)

**Answer: C**

6. You have installed a new BayStack 460-24T switch into a customer's network and are using the QoS Wizard to configure the QoS settings for various IP traffic flows. Which two IP applications can you directly choose in the QoS Wizard to prioritize inbound frames based on traffic type? (Choose two.)

- A. E-mail (SMTP)
- B. File Transfer (FTP)
- C. Multicasting (IGMP)
- D. Trivial File Transfer (TFTP)
- E. Network Management (SNMP)

**Answer: AB**

7. On a BayStack 470 switch you need to disable Internet Group Management Protocol (IGMP) snooping

for a customer's VLAN (100). Using the Console Interface (CI) Menus, how should you accomplish this task?

- A. From the VLAN configuration screen disable IGMP proxy for VLAN 100.
- B. From the VLAN configuration screen disable IGMP snooping for VLAN 100.
- C. From the VLAN configuration screen, configure the VLAN setup of port 100.
- D. From the Switch configuration screen choose IGMP configuration and disable IGMP snooping for VLAN 100.

**Answer: B**

8. Given the following information:

A customer has a stack of four BayStack BPS switches configured in pure mode and functioning properly. Two BayStack 450-24T switches are added to the stack to increase its capacity and the BayStack BPS stack operation mode is changed to hybrid.

After rebooting the stack, it appears to be functioning properly but, all VLAN configurations have been lost.

What is the most likely cause of this issue and which action should you take to resolve it?

- A. A BayStack 450-24T has incorrectly been assigned as the base unit. Define a BayStack BPS as the base unit and power cycle the stack to resolve the issue.
- B. The Interoperability Software Version Number (ISVN) of the BayStack 450-24T software does NOT match the ISVN of the BayStack BPS software. Upgrade the BayStack 450-24T software to resolve the issue.
- C. A hybrid stack only supports 64 VLANs. If more are defined on a pure BayStack BPS stack, when you change to hybrid mode you will lose all the VLANs. A maximum of 64 VLANs can be re-entered to resolve the issue.
- D. When changing from a pure to a hybrid stack, the VLAN configuration will always be lost. Before changing to hybrid mode, the configuration file must be downloaded to a TFTP server, and then uploaded after changing to hybrid mode.

**Answer: C**

9. Given the following information:

A BayStack 460-24T-PWR switch is delivering Power over Ethernet (PoE) to a number of devices

connected to it.

Currently, all devices that are connected to the switch and require PoE are functioning properly.

The switch is connected to both internal and external power sources.

The external power source is a BayStack 10 Power Supply Unit (PSU).

Currently, "DC Source Type" is set to "BayStack 10" (BayStack 10 PSU) and "DC Source Configuration" is set to "RPSU" (Redundant Power Supply Unit) on the switch.

A new device that requires PoE is connected to the switch and fails to power on.

The "DTE Power Source" LED for the port used to connect the device then begins to blink amber. Assume that prior to connecting the device to the switch it was tested in the lab and is known to be functioning correctly.

What is the most likely cause of this issue and which action should you take to resolve it?

- A. The port is administratively disabled. Administratively enable the port to correct the issue.
- B. NO Data Terminating Equipment (DTE) has been detected on the port. Check the port and correct a cabling fault to resolve the issue.
- C. There is a power fault or short circuit on the port. The port or the cable may be faulty. Connect the device to a different port. If functioning normally, check the cables and correct a possible cabling fault to resolve the issue.
- D. The Data Terminating Equipment (DTE) has been detected on the port, but there is insufficient power to turn the device on. Change the "DC Source Configuration" setting to "Power Sharing" to provide more PoE for the switch.

**Answer: D**

10. How do you configure VLAN port membership on a BayStack 425 10/100/1000 series switch? (Choose two.)

- A. Run the QoS Wizard to create new VLAN port members.
- B. Access the VLAN configuration screen of the Console Interface (CI) Menu.
- C. Create an ASCII configuration file with the required VLAN membership configuration.
- D. Use Java Device Manager (JDM) to make the selected ports members of the VLANs.

**Answer: BD**

11. A customer with a BayStack 470-24T switch wants to configure MAC address-based security. Given that they can create up to 10 MAC Destination Addresses (DA) to filter, how are all packets with specified DAs treated?

- A. All packets with specified DAs are dropped.
- B. All packets with specified DAs are dropped based on ingress port.
- C. All packets with specified DAs are dropped based on VLAN membership.
- D. All packets with specified DAs are dropped based on source address intrusion.

**Answer: A**

12. What is the condition under which the Single Fiber Fault Detection (SFFD) feature should be enabled for BayStack 470 switch? Assume that Nortel Networks devices are at both ends of a gigabit Ethernet fiber link.

- A. When both ports making up the link are implemented using the BayStack 450 MDA.
- B. When both of the ports making up the link are implemented using the BayStack 470 Gigabit ports.
- C. When at least one of the ports making up the link is implemented using a BayStack 470 Gigabit port.
- D. When at least one of the ports making up the link is implemented using the BayStack 450 Gigabit MDA.

**Answer: C**

13. Port-based Virtual LAN (VLAN) 10 has been configured on a standalone BayStack 5510-24T switch. Port 5 must now be added to VLAN 10. What are the steps necessary to add Port 5 to VLAN 10 in Java Device Manager (JDM)?

- A. From the main menu choose Edit > VLANs . Double click on Port Members for VLAN 10 and add Port 5 to the list of members. Finally, click Apply .
- B. From the main menu choose VLAN > VLANs . Double click on Port Members for VLAN 10 , and add Port 5 to the list of members. Finally, click Apply .
- C. Highlight Port 5 on the device and from the main menu choose Edit>Port . Now click on the VLAN tab and in the DefaultVlanId field enter 10 . Finally, click Apply .
- D. From the main menu choose Application > VLAN > VLAN Configuration . In the VLAN Table section, click the Modify icon for VLAN 10 . Now add Port 5 to the list of members and click Apply .

**Answer: B**

14. The library of a large tech school offers a network connection area for free roaming students to connect to the schools network with their portable devices. The BayStack switch supporting this service offers several Enhanced Authentication Protocol (EAP) configured port groups. To maintain this access area for registered students only, the school should assign these ports to which EAP group?

- A. EAP Group 1 - Administrative Status set to Auto
- B. EAP Group 2 - Administrative Status set to Disabled
- C. EAP Group 3 - Administrative Status set to Force Authorized
- D. EAP Group 4 - Administrative Status set to Force Unauthorized

**Answer: A**

15. A company has three BayStack 450-24T switches. The switches are labeled SW1, SW2 and SW3. Each switch has a BayStack 400-ST1 Cascade Module installed. You have been asked to stack the switches in a stack-down configuration with switch SW1 positioned at the top of the stack. How would you physically connect the cascade cables to each of the switches and set the Unit Selector switch? (Choose two.)

- A. Set the Unit Selector switch of SW1 in the up position. Set the Unit Selector switch of SW2 and SW3 in the down position.
- B. Set the Unit Selector switch of SW3 in the up position. Set the Unit Selector switch of SW1 and SW2 in the down position.
- C. Connect Cascade A Out of SW3 to Cascade A In of SW2. Connect Cascade A Out of SW2 to Cascade A In of SW1. Connect Cascade A Out of SW1 to Cascade A In of SW3.
- D. Connect Cascade A Out of SW3 to Cascade A In of SW1. Connect Cascade A Out of SW1 to Cascade A In of SW2. Connect Cascade A Out of SW2 to Cascade A In of SW3.

**Answer: AD**

Visualexams.com was founded in 2006. The safer,easier way to help you pass any IT Certification exams . We provide high quality IT Certification exams practice questions and answers(Q&A). Especially Adobe, Apple, Citrix, Comptia, EMC, HP, HuaWei, LPI, Nortel, Oracle, SUN, Vmware and so on. And help you pass any IT Certification exams at the first try.

Web site: <http://www.visualexams.com>

You can reach us at any of the email addresses listed below.

E-Mail: [visualexams \(at\) hotmail.Com](mailto:visualexams@hotmail.com)