

Exam : NORTEL 920-141

**Title : NNCDS-Communication
Server(cs)1000 release 4.0**

Version : Demo

Important Note, Please Read Carefully

Other VisualExams products

[All visual exams IT Exam Products](#)

Our products of Offline Testing Engine

Use the offline Testing engine product to practice the questions in an exam environment.

Build a foundation of knowledge which will be useful also after passing the exam.

[visual exams Testing Engine](#)

Latest Version

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 90 days after the purchase. You should check your member zone at VisualExams and update 3-4 days before the scheduled exam date.

Here is the procedure to get the latest version:

1. Go to <http://www.visual exams.com/>
2. Log in the **User Center**
3. The latest versions of all purchased products are downloadable from here. Just click the links.

Feedback

If you spot a possible improvement then please let us know. We always interested in improving product quality.

Feedback should be send to Visual exams@hotmail.com. You should include the following: Exam number, version, page number, question number, and your login Account.

Our experts will answer your mail promptly.

Explanations

This product does not include explanations at the moment. If you are interested in providing explanations for this exam, please contact Visual exams@hotmail.com.

Features

- Comprehensive questions with complete details
- Instant Downloadable in PDF form.
- Verified Answers Researched by Industry Experts
- Questions accompanied by exhibits.
- Drag and Drop questions as experienced in the Actual Exams.
- These questions and answers are backed by our GUARANTEE.
- Questions updated on regular basis.
- Like actual certification exams our product is in multiple-choice questions (MCQs)

Commitment to Your Success: At VisualTestExam.com, we are committed to you ongoing success. Our exams and questions are constantly being updated and compared to industry standards.

Want to earn a Microsoft certification like [MCSE](#), [MCSE 2003](#), [CCNA](#), [CCNP](#)? Thinking about getting an [A+](#) or [CCSP](#)?

A, [CCSP](#) or [Network+](#) Certification with less effort and time. You will be astonished at the theoretical and practical knowledge you will acquire in such a short period of time using our Certification Training Products. Our Study material will enable you to pass your [Microsoft](#), Your [Cisco](#) and any other certification on the very first attempt.

Guarantee

VisualExams provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if somehow you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

1. A customer wants to configure the Enterprise Media Gateways (EMG) on their CS 1000 RIs. 4.0 system for survivability. They also need to interpret the network requirements for the system. Which configuration ensures network survivability?

- A. The survivable EMG TLAN IP address must be on the same TLAN subnet as the Call Server.
- B. The survivable EMG ELAN IP address must be on the same ELAN subnet as the Call Server.
- C. The survivable EMG ELAN IP address must be on a different ELAN subnet than the Call Server.
- D. The survivable EMG must be separated from the Call Server by a Layer 3 device networked with the two Call Servers.

Answer: B

2. A customer is considering the deployment of the a H.323 Gatekeeper in failsafe mode for a CS 1000 RIs. 4.0 solution. Which statement most accurately describes why you would recommend this configuration?

- A. Communication to the primary and secondary H.323 Gatekeepers will never be lost.
- B. The Failsafe H.323 Gatekeeper within a gatekeeper zone takes over gatekeeper responsibilities for all of its peers within the zone.
- C. If communication is lost with the primary H.323 Gatekeeper, the secondary gatekeeper will become the primary and run in failsafe mode.
- D. If communication is lost to both gatekeepers, the H.323 Gateway running the failsafe gatekeeper services will continue to route calls in a best-effort fashion until communication is restored.

Answer: D

3. A company is planning the deployment of a new CS 1000 RIs. 4.0 system and requires ultra-high reliability. How would campus redundancy meet their needs?

- A. It provides an optionally redundant Signaling Server.
- B. It moves the Gatekeeper to a standalone Signaling Server.
- C. It duplicates the entire processing core of a CS 1000E fault resilient system.
- D. It provisions an Enterprise Media Gateway 1000E as a CS 1000E Call Server.

Answer: C

4. In the process of provisioning a CS 1000S RIs. 4.0 system, a customer wants to include a branch office

into the configuration with 50 analog and 400 IP Phones. Each IP Phone carries 6 Centi-Call Seconds (CCS) each; 50% of the calls go to other IP Phones and 50% go to analog telephones. The Voice Gateway Media Cards (VGMCs) for the Enterprise Media Gateway 1000B have a call capacity of 794 CCS. How many VGMCs will be needed?

- A. one
- B. two
- C. three
- D. four

Answer: A

5. What is a the benefit of networking several CS 1000S RIs 4.0 system Call Servers together through LAN or WAN connections under the control of one Network Redirect Server (NRS)?

- A. Double Virtual Trunk resources are used for intra-system, inter-Call Server calls.
- B. IP Phones with a known community of interest can be registered on the same Call Server.
- C. AMIS and VPIM networking of the voice messaging systems is more efficient using the NRS.
- D. MCDN can be enabled providing Enterprise-wide feature transparency between the systems.

Answer: D

6. When designing a geographic redundancy scheme for a CS 1000M RIs. 4.0 system, the failsafe Network Routing Service (NRS) must reside on which component in case network communications are lost with the Primary and Alternate NRS?

- A. the Signaling Server designated as the Leader
- B. the Signaling Server designated as the Follower
- C. on both the Follower and the Leader Signaling Server
- D. the CS 1000E Call Server that resides on the secondary system

Answer: A

7. A company has a geographically dispersed workforce with laptop computers. They connect their PCs to the company intranet via cable modems and/or DSL over VPN using IPSec. They plan to deploy IP Softphone 2050s. A network assessment shows some shared Ethernet hubs between the VPN server and

the CS 1000 RIs. 4.0. At a minimum, what is required to enable a deployment of the telephones?

- A. Layer 3 switches with gigabit uplink
- B. Layer 3 switches with VLAN support
- C. Layer 2 switches with 802.1p support
- D. Layer 2 switches with DiffServ capabilities

Answer: C

8. A company plans to deploy a CS 1000M-SG RIs. 4.0 system at their headquarters. Some of their call center agents are located in a branch office. They want all applications to be centrally located and managed at the headquarters. Agents are to access services via an IP connection and get local access to the PSTN through PRI connections. What should the company consider as part of their traffic plan? (Choose three.)

- A. the number of PRI cards for ESN access
- B. the creation of private zone for the agents
- C. the engineering requirements for Multimedia Processing Units (MPUs)
- D. the total WAN requirements for data between the branch office and the main office
- E. the total WAN bandwidth required for the remote call center agent telephony needs

Answer: BDE

9. In the process of designing a CS 1000 RIs. 4.0 system per the customer specifications, you need to order two Enterprise Media Gateway 1000T (EMG 1000T) and eight EMG 1000E systems. Each EMG 1000T will have three digital trunk cards (TMDI) and the EMG 1000E systems are provisioned for digital and analog lines. At a minimum, how many Clock Controllers are required?

- A. two
- B. three
- C. six
- D. ten

Answer: A

10. A customer has a CS 1000M-SG RIs. 4.0 system installed with one Signaling Server with 512 MB of memory. This system networks to multiple sites with VoIP using 200 IP Peer H.323 trunks. Because

additional sites have been added, the customer needs to expand this network. To configure an additional 200 IP Peer H.323 trunks, what must be done?

- A. Add one IP Trunk card.
- B. Just configure the additional trunks.
- C. Add one additional Signaling Server.
- D. Just purchase additional virtual trunk licenses.

Answer: D

Visualexams.com was founded in 2006. The safer,easier way to help you pass any IT Certification exams . We provide high quality IT Certification exams practice questions and answers(Q&A). Especially Adobe, Apple, Citrix, Comptia, EMC, HP, HuaWei, LPI, Nortel, Oracle, SUN, Vmware and so on. And help you pass any IT Certification exams at the first try.

Web site: <http://www.visualexams.com>

You can reach us at any of the email addresses listed below.

E-Mail: [visualexams \(at\) hotmail.Com](mailto:visualexams@hotmail.com)