

Exam : SolarWinds SCP-500

**Title : SolarWinds Certified
Professional Exam**

Version : Demo

Important Note, Please Read Carefully

Other VisualExams products

[All visualexams IT Exam Products](#)

Our products of Offline Testing Engine

Use the offline Testing engine product to practice the questions in an exam environment.

Build a foundation of knowledge which will be useful also after passing the exam.

[visualexams Testing Engine](#)

Latest Version

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 90 days after the purchase. You should check your member zone at VisualExams and update 3-4 days before the scheduled exam date.

Here is the procedure to get the latest version:

1. Go to <http://www.visualexams.com/>
2. Log in the **User Center**
3. The latest versions of all purchased products are downloadable from here. Just click the links.

Feedback

If you spot a possible improvement then please let us know. We always interested in improving product quality.

Feedback should be send to visualexams@hotmail.com. You should include the following: Exam number, version, page number, question number, and your login Account.

Our experts will answer your mail promptly.

Explanations

This product does not include explanations at the moment. If you are interested in providing explanations for this exam, please contact visualexams@hotmail.com.

Features

- Comprehensive questions with complete details
- Instant Downloadable in PDF form.
- Verified Answers Researched by Industry Experts
- Questions accompanied by exhibits.
- Drag and Drop questions as experienced in the Actual Exams.
- These questions and answers are backed by our GUARANTEE.
- Questions updated on regular basis.
- Like actual certification exams our product is in multiple-choice questions (MCQs)

Want to earn a Microsoft certification like [MCSE](#), [MCSE 2003](#), [CCNA](#), [CCNP](#)? Thinking about getting an [A+](#) or [CCSP](#)?

A, [CCSP](#) or [Network+](#) Certification with less effort and time. You will be astonished at the theoretical and practical knowledge you will acquire in such a short period of time using our Certification Training Products. Our Study material will enable you to pass your [Microsoft](#), Your [Cisco](#) and any other certification on the very first attempt.

Guarantee

Visualexams provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

1. The data center team requires that they be alerted if any of the servers in a remote site go down. However, they do NOT want to receive alerts when the remote site connection goes down.

Which two configuration steps should you take within your network management system (NMS) to meet these requirements? (Choose two.)

- A. set up alerts on server status
- B. set up alerts on the remote connection status
- C. set each of the servers as dependencies for each other
- D. set up the remote connection as a dependency for each of the servers
- E. set up alerts on the remote router status

Answer: AD

2. What is an advantage of using SNMPv2c over using SNMPv1?

- A. username parameter
- B. get bulk command
- C. get next command
- D. 32 bit counters
- E. authentication and encryption

Answer: B

3. Which two variables are used in the calculation of Percent Utilization? (Choose two.)

- A. configured bandwidth
- B. packets per second
- C. buffer overruns
- D. interface discards
- E. bits per second

Answer: AE

4. Due to a server crash, you had to move Orion to a new server with a new IP address.

Which two changes should you make to ensure that Orion functions properly from the new server and IP

address? (Choose two.)

- A. update the access control lists (ACLs) that restrict management protocols
- B. change the IP address specified in the snmpd.conf file on the Orion server
- C. update the source address for NetFlow packets exported to Orion
- D. notify ARIN of the Orion server's new IP address
- E. update the destination IP address for Syslog and SNMP traps on your managed devices

Answer: AE

5. You are monitoring your Internet connection, and your ISP has guaranteed 512 Kbps. Historical data shows that your connection speed holds at 256 Kbps for long periods of time, but never exceeds this speed.

What does this indicate?

- A. The ISP has misconfigured the link.
- B. The WAN router is misconfigured.
- C. The NAT table is overloaded.
- D. QoS is dropping low priority traffic.

Answer: A

6. Your current deployment has multiple Orion NPM servers monitoring multiple locations from a single site. This is producing inaccurate data and high WAN bandwidth utilization.

What are the two most efficient ways to address this issue? (Choose two.)

- A. deploy Orion NPM at each remote location
- B. deploy Orion Enterprise Operations Console
- C. deploy an additional Orion Poller
- D. deploy an additional Orion Web Server
- E. deploy an Orion Hot Standby

Answer: AB

7. How does the Orion Universal Device Poller (UnDP) monitor a device's statistics that are not included in the standard Orion NPM MIB database?

- A. by manually associating the device's OID to Orion

- B. by keeping a copy of the device's MIB on the Orion NPM Server
- C. by automatically searching the common MIB repositories and updating Orion
- D. by manually compiling the MIB into the Orion MIB database
- E. by manually compiling the OID into the Orion MIB database

Answer: A

8. Which protocol should a network engineer enable on routers and switches to collect utilization statistics?

- A. ICMP
- B. SNMP
- C. SMTP
- D. WMI

Answer: B

9. A network engineer is enabling SNMP on their network devices and needs to ensure it will use message integrity.

Which version of SNMP should they use?

- A. SNMPv1
- B. SNMPv2c
- C. SNMPv3
- D. SNMPv4

Answer: C

10. A network engineer notices the Syslog server's database is growing significantly in size due to the large number of devices sending Syslog messages.

What should the engineer do to control database growth?

- A. configure the Syslog server to discard unwanted messages
- B. configure the devices and the Syslog server to use TCP-based Syslog
- C. configure the devices and the Syslog server to use SNMPv3
- D. configure the Syslog server to capture SNMP traps instead of Syslog

Answer: A

11. You have recently implemented a VoIP infrastructure within the company network. You are receiving trouble tickets indicating calls are dropping between their New York and San Francisco offices.

Which two IP service level agreement (SLA) measurements should you use to identify the cause of the issue?

- A. latency
- B. SIP
- C. NetFlow
- D. available bandwidth
- E. jitter

Answer: AE

12. Which two performance metrics can be affected by proper QoS implementation? (Choose two.)

- A. jitter
- B. shaping
- C. marking
- D. queuing
- E. latency

Answer: AE

13. Which network protocols are used by SolarWinds products during network discoveries?

- A. ICMP and SMTP
- B. DHCP and TFTP
- C. PPTP and IMAP
- D. ICMP and SNMP

Answer: D

14. Which two management protocols should you use to measure the effectiveness of your QoS implementation? (Choose two.)

- A. Syslog

- B. SNMP
- C. NetFlow
- D. WMI
- E. SSHv2

Answer: BC

15. Which management protocol should you use to analyze network traffic in and out of a router interface?

- A. WMI
- B. Syslog
- C. IP service level agreement (SLA)
- D. sFlow

Answer: D

16. Users are complaining that a network connection is slow.

How should SNMP be used to verify performance of the interface?

- A. verify bandwidth usage via ifInOctets
- B. verify status via the ifTable
- C. verify that SNMP agent is responding
- D. verify the performance via ifSpeed

Answer: A

17. Orion NPM is monitoring the performance of DS-3 utilizing standard MIBs in the ifTable. Occasionally, the reported traffic rates for this interface spike well above 45 Mbps.

What is the most likely cause?

- A. heavy network traffic
- B. carrier misconfiguration
- C. counter rollovers
- D. database issues

Answer: C

18. Orion NPM is using SNMP to poll a router and track interface traffic rates. The data are collected every 5 minutes, and the most recent values collected for a specific interface are 1,000,000 and 2,000,000 octets.

What is the approximate average rate of traffic for this interface?

- A. 1 Kbps
- B. 3 Kbps
- C. 16 Kbps
- D. 26 Kbps

Answer: D

19. When using a network management system (NMS) to monitor network interfaces on a router, you notice that statistics are wrong after an interface card is physically removed from the device.

What has most likely caused this problem?

- A. interface re-indexing
- B. device configuration
- C. counter rollovers
- D. access lists

Answer: A

20. Which two reporting requirements should you consider when specifying data roll-up settings for a network management system (NMS)? (Choose two.)

- A. data encryption
- B. data format
- C. data granularity
- D. monitoring coverage
- E. data retention

Answer: CE

21. Which advantage do SNMP traps and Syslog have over SNMP polling?

- A. reliability of event detection
- B. ability to poll events in real-time

- C. ease of configuration
- D. speed of event detection

Answer: D

22. How can you use a network management system (NMS) to ensure service level agreement (SLA) parameters are realistic for your environment?

- A. increase data collection period
- B. configure data summarization
- C. reduce data retention period
- D. baseline network performance

Answer: D

23. Your service level agreement (SLA) dictates that you must be able to notify the appropriate parties when systems are down for over 2 minutes and report on data for the last 120 days. Your network management system (NMS) has been configured to collect status every 10 minutes and summarize and retain data for 90 days.

Which two settings should you change in the NMS to meet the business requirements? (Choose two.)

- A. increase data retention to 120 days
- B. configure status polling to occur every 5 minutes
- C. summarize hourly data into weekly data every 120 days
- D. configure status polling to occur every minute
- E. summarize hourly data into weekly data every 90 days

Answer: AD

24. What should you do to track whether a new configuration has alleviated slow network performance?

- A. compare ICMP availability before and after the change
- B. compare application responsiveness before and after the change
- C. monitor the affected devices for stability
- D. monitor bandwidth utilization on affected interfaces

Answer: B

25. The IT budgeting department has asked you for reports that will help them better plan for increases in monthly recurring costs.

Which report should you set up to help the IT budgeting department meet this objective?

- A. router inventory
- B. WAN interface utilization
- C. LAN interface utilization
- D. available switch ports

Answer: B

26. IT management wants to know how they can lower their total power consumption by consolidating equipment and shutting off unnecessary equipment.

Which type of report can you create to help them plan for this?

- A. bandwidth utilization
- B. available switch ports
- C. router CPU utilization
- D. total NetFlow endpoints

Answer: B

27. The IT planning department has asked for a report to help them understand when they need to implement IPv6.

Which report would offer them the greatest amount of relevant information?

- A. unique NetFlow exporters
- B. DHCP server CPU utilization
- C. number of subnets
- D. IP address utilization trends

Answer: D

28. You are planning a network management implementation where the network has several low bandwidth WAN links.

Which two network management protocols are most likely to cause heavy traffic on WANs and should therefore be considered carefully before deployment? (Choose two.)

- A. Syslog
- B. SSH
- C. SMTP
- D. NetFlow
- E. ICMP

Answer: AD

29. Which two sources provide detailed visibility into router interface traffic? (Choose two.)

- A. SNMP statistics
- B. SNMP traps
- C. NetFlow
- D. Syslog
- E. CDP

Answer: AC

30. A network engineer is planning to deploy a network management system (NMS) to monitor a network. Which two UDP ports should be enabled in router access control lists and firewalls so the NMS can effectively monitor devices? (Choose two.)

- A. 160
- B. 161
- C. 162
- D. 163
- E. 164

Answer: BC

Visualexams.com was founded in 2006. The safer,easier way to help you pass any IT Certification exams . We provide high quality IT Certification exams practice questions and answers(Q&A). Especially Adobe, Apple, Citrix, Comptia, EMC, HP, HuaWei, LPI, Nortel, Oracle, SUN, Vmware and so on. And help you pass any IT Certification exams at the first try.

Web site: <http://www.visualexams.com>

You can reach us at any of the email addresses listed below.

E-Mail: [visualexams \(at\) hotmail.Com](mailto:visualexams@hotmail.com)